

# WISA®-Parquet Veneer

WISA-Parquet Veneer is a fit-to-purpose component as base veneer for three layer parquets. WISA-Parquet Veneers are ready for customer's manufacturing process immediately after received, since veneer moisture level has been balanced in advance.

## Product

Veneer made of spruce (Picea Abies)

## Thickness

2.0 mm thick veneer as standard.

## Quality

Standard parquet quality

Sound knots allowed

Open knot diameter max. 40 mm

Split length max. 500 mm and width max. 10 mm

## Veneer sizes

Veneers are cut according to customer specifications. Lengths are possible up to 2540 mm and widths up to 1350 mm. Minimum size is 1200 x 100 mm.

## Moisture Controlled Veneers

Customer's manufacturing process becomes more efficient as the veneers are ready for use right after received. Moisture balance in veneers is achieved by state of art moisture balance technology. The moisture is continuously monitored by a computer aid control system and every veneer sheet is balanced individually.

## Packaging

Veneer pallets are sealed with plastic foil to secure the right moisture and quality to our customers. Veneer pallet is protected with hermetic packaging from all six faces. Veneers should be stored flat in a dry covered place.





### Tolerances

	Standard Range	Tolerance
Thickness (mm)	2	+0.2/- 0.1
Length (mm)	1200 – 2540	+5/- 0
Width (mm)	150 – 799	+5/- 0
	800 – 1350	+10/- 0
<b>Moisture content (%)</b>		
Standard	2 – 8	±2 % unit
Moisture controlled	4, 5, 6, 7, 8	±1 % unit

### Veneer properties

Our veneers go through constant quality securing process in all stages of the production. Dimensions, moisture and quality are measured several times to secure the right grade. Thin but strong veneer balances the three layer parquet construction and keeps it straight.

Our production aims to fulfil customer needs and constantly develops products and services in tight co-operation with our sales and R&D department.

### Environment

WISA products are manufactured in Europe according to the strictest sustainability principles. By choosing WISA, our customers have the confidence that their plywood and veneer come only from legal sources and conform to all relevant standards and regulations, including the European Union Timber Regulation (EUTR).

More with Biofore. UPM leads the integration of bio and forest industries into a sustainable future characterized by innovation, responsibility and resource efficiency.

For further information please visit [www.wisaplywood.com](http://www.wisaplywood.com)



#### UPM Plywood

Niemenkatu 16  
 P.O. Box 203  
 FI-15141 Lahti  
 Finland  
 Tel. +358 204 15 113  
 Fax +358 204 15 112  
[plywood.sales@upm.com](mailto:plywood.sales@upm.com)

[www.wisaplywood.com](http://www.wisaplywood.com)  
[www.upm.com](http://www.upm.com)

UPM policy is one of continuous development. We reserve the right to amend specifications without notice or obligation.